

# Model LC500

**lifeclinic**  
Health Management Systems

Better Health Through Awareness.

## Capabilities...

- **Internet Ready:** easy integration into any network for real-time collection and management of data, or utilize the Group-Stat® system for increased data management capabilities
- **Body Fat:** body composition measured accurately using noninvasive bioimpedance method
- **Oximeter:** provides real-time evaluation of blood oxygen levels
- **Barcode Reader:** provides convenient employee/loyalty card identification
- **Magnetic Stripe Reader:** supports magnetic stripe based identification cards
- **Peripheral Input Ports:** Infrared and USB (standard & mini) for interfacing with personal health devices



To contact a Lifeclinic representative in your area, call: 800.543.2850

[www.lifeclinic.com](http://www.lifeclinic.com)

## Features

- Blood Pressure, Pulse Rate and Weight
- Fully Automated Upper Arm Pressure Cuff
- Oscillometric Methodology
- Proven Accuracy Meets AAMI Standards
- Electronic Scale
- 10.4" Touchscreen LCD Display
- Wheelchair Accessibility (Optional)
- Interactive Health Information Screens
- Color-coded Results Charts
- Four Information Display Panels
- Optional 2.25" Printer Available

# Model LC500

**lifeclinic**  
Health Management Systems

Better Health Through Awareness.

## SPECIFICATIONS

### **Equipment**

Class II medical device manufactured in FDA-regulated, ISO 13485:2003-registered Lifeclinic facility

### **Blood Pressure Measurement**

**Method:** Oscillometric

#### **Accuracy**

Complies with AAMI (Association for the Advancement of Medical Instrumentation) Standards

+/- 5 mmHg (millimeters of mercury)

#### **Range**

Systolic: +40 to +260 mmHg

Diastolic: +20 to +200 mmHg

Pulse: 30 bpm to 220 bpm

**Rate of Cuff Inflation:** Approximately 8 mmHg/sec

**Overpressure Limit:** 310 +/- 10 mmHg

#### **Temperature**

Operating: 50 to 104° F (10 to 40° C)

Storage: -40 to 131° F (-40 to 55° C)

#### **Humidity**

Operating: 15 to 95% (noncondensing)

Storage: 15 to 95% (noncondensing)

### **Weight Measurement**

**Range:** 40 to 440 lbs. (18.2 to 200 kg)

**Accuracy:** +/- 1 lb. (+/- 0.5 kg)

### **Body Fat Measurement**

**Method:** Bioimpedance

**Accuracy:** +/- 3%

### **Blood Oxygen Measurement**

**Method:** Infrared

**Accuracy:** +/- 2%

### **Input Power Requirements**

Switch selectable 120/240 VAC - 50/60Hz

2.5 amps

3-wire grounded outlet



### **Physical Dimensions**

Height: 68.0 in. (170.0 cm)

Width: 33.5 in. (85.1 cm)

Depth: 25.0 in. (63.5 cm)

Weight: 100 lbs. (45.5 kg)